

### Transport Platforms (TP) Safety Tips


The Transport Platform is a tool of the trade used to move authorized and trained personnel with their materials and tools between levels at a worksite.

- TP's should be operated, used, erected and dismantled only by personnel who have been properly trained and familiarized with the specific model / machine. Only people who are authorized and have received the required training are permitted on the TP.
- A pre-start inspection must be completed at the beginning of each shift prior to use.
- Do not exceed the maximum load limitations, including both personnel and material for the configuration of the TP being used.
- Make sure that all inspections and maintenance are performed as required and according to manufacturer's instructions.
- When dismantling do not remove the wall ties unless the base and remaining ties can support the TP configuration without tipping.
- Ensure the TP operates at a minimum travel distance of 18" from the building or structure.
- When moving the TP always look in the direction of travel. Ensure there are no personnel or material beneath the platform.
- When descending, ensure the TP stops automatically no less than 10' above the supporting level for at least 3 seconds and sounds a continuous warning from that point until the bottom is reached.
- Always install guardrails and mast guards. Ensure access gates and other access locations are protected with guardrails.

### Transport Platforms (TP) Safety Tips

- Ensure that no material or personnel project beyond or overhang the platform guardrails.
- Use all required personal fall protection equipment during erection and dismantling.
- Only use normal operating controls for the TP. Do not bypass or override the normal operating controls or safety devices.
- Check for hazards such as overhead obstructions, building protrusions, high voltage lines, inadequate base support, drop off's, debris and other unsafe conditions.
- If jobsite conditions dictate and when transporting personnel, a roof shall be fitted to the TP, to protect from falling objects.

\*For guidance on training contact the manufacturer. For additional guidance on training refer to ANSI A92.10-2009 or OSHA Regulations.



***Through the OSHA and Scaffold Industry Association (SIA) Alliance, SIA developed this Tip Sheet for informational purposes only. It does not necessarily reflect the official views of OSHA or the U.S. Department of Labor. Feb. 2010.***